


Measurement Adapters

RL-120, WX-120D



FEATURES


- Precision Measurement adapter
- Modular Connector System
- 7-16 Female or N Female (through adapter) measurement connector

SPECIFICATIONS

Return Loss (VSWR)	> 40 dB (1.02)	
Environmental Conditions	-5 to +55°C (+23 to +131°F), IP60	
Code	D-SC150	
Adapter Connection ⁽⁸⁾	D-PC150S	RL-120 <i>FastLine</i> Socket
	D-PC150X	RL-120 <i>FastLine</i> Flange ⁽¹⁴⁾
	D-PC150T	RL-120 <i>Fast Line</i> Plug
Measurement Connector	D-PC32E1	7-16 Precision Female
Options	O-NNB.06	Flange screw set
	O-NEC.02	7-16 Male - N Female Precision Adapter

⁽⁸⁾ Other Connections available ⁽¹⁴⁾ Inner Connections not included

6+1/8", WX-152D



FEATURES

- Precision Measurement adapter
- Modular Connector System
- 7-16 Female or N Female (through adapter) measurement connector

SPECIFICATIONS

Return Loss (VSWR)	> 40 dB (1.02)	
Environmental Conditions	-5 to +55°C (+23 to +131°F), IP60	
Code	D-SC150	
Adapter Connection ⁽⁸⁾	D-PC150U	6+1/8" <i>FastLine</i> Socket
	D-PC150V	6+1/8" <i>FastLine</i> Flange ⁽¹⁴⁾
	D-PC150W	6+1/8" <i>FastLine</i> Plug
Measurement Connector	D-PC32E1	7-16 Precision Female
Options	O-NNB.05	Flange screw set
	O-NEC.02	7-16 Male - N Female Precision Adapter

⁽⁸⁾ Other Connections available ⁽¹⁴⁾ Inner Connections not included