


25 mm Panel Connectors

N Female



FEATURES


- Modular Connector System

SPECIFICATIONS

Max RMS Power ⁽³⁾	UHF	500 W	(700 MHz)
	VHF B.III	900 W	(230 MHz)
	VHF B.I	1.4 kW	(88 MHz)
	FM	1.3 kW	(108 MHz)
Return Loss (VSWR)	> 40 dB (1.02)		
Environmental Conditions	-5 to +55°C (+23 to +131°F), IP60		
Mounting Screws (Included)	4 x M3x6 (Tx10 Torx)		
Code	D-PC25C N Female		
	D-PC25C3 N Angular Female		

⁽³⁾ Altitude < 1500 m (4,900 ft.), Free air, Ambient temp. < 30 °C (86 °F)

N Male



FEATURES


- Modular Connector System

SPECIFICATIONS

Max RMS Power ⁽³⁾	UHF	500 W	(700 MHz)
	VHF B.III	900 W	(230 MHz)
	VHF B.I	1.4 kW	(88 MHz)
	FM	1.3 kW	(108 MHz)
Return Loss (VSWR)	> 40 dB (1.02)		
Environmental Conditions	-5 to +55°C (+23 to +131°F), IP60		
Mounting Screws (Included)	4 x M3x6 (Tx10 Torx)		
Code	D-PC25D N Male		

⁽³⁾ Altitude < 1500 m (4,900 ft.), Free air, Ambient temp. < 30 °C (86 °F)

7-16 Female



FEATURES


- Modular Connector System

SPECIFICATIONS

Max RMS Power ⁽³⁾	UHF	2.0 kW	(700 MHz)
	VHF B.III	3.5 kW	(230 MHz)
	VHF B.I	5.6 kW	(88 MHz)
	FM	5.1 kW	(108 MHz)
Return Loss (VSWR)	> 40 dB (1.02)		
Environmental Conditions	-5 to +55°C (+23 to +131°F), IP60		
Mounting Screws (Included)	4 x M3x6 (Tx10 Torx)		
Code	D-PC25E 7-16 Female		

⁽³⁾ Altitude < 1500 m (4,900 ft.), Free air, Ambient temp. < 30 °C (86 °F)

7-16 Male



FEATURES

- Modular Connector System

SPECIFICATIONS

Max RMS Power ⁽³⁾	UHF	2.0 kW	(700 MHz)
	VHF B.III	3.5 kW	(230 MHz)
	VHF B.I	5.6 kW	(88 MHz)
	FM	5.1 kW	(108 MHz)
Return Loss (VSWR)	> 40 dB (1.02)		
Environmental Conditions	-5 to +55°C (+23 to +131°F), IP60		
Mounting Screws (Included)	4 x M3x6 (Tx10 Torx)		
Code	D-PC25F 7-16 Male		

⁽³⁾ Altitude < 1500 m (4,900 ft.), Free air, Ambient temp. < 30 °C (86 °F)